



# SuperTag Alarming 2-Tone Pin

Add an extra level of security to your highvalue, high-risk merchandise—anywhere in the store. This alarming 2-tone SuperTag provides top-of-the-line protection for everything from heavy outerwear to delicate intimate garments. It's sleek shape does not detract from high-end items, yet provides a strong visual deterrent. The alarming feature reduces risk of theft when protected merchandise is out of staff's view. The tag will emit an audible alarm if defeat is attempted and will alarm the AM pedestal system if protected products pass through the detection zone. The tag alarm will stop once the battery is depleted or tag is reset.

#### **Retailer Values**

- // 2-tone alarming feature adds an extra layer of security to high-value, high-risk merchandise
- // Supertag, the gold standard in asset protection, features a patented clamp design for superior defeat resistance
- Sleek, aesthetic design helps minimize impact to merchandise on display
- // Backed by a multi-year battery life warranty to reduce operational and replacement costs

## **Solution Application**

Electronics, Leather, Luxury Goods, Handbags, Sporting Goods, Power Tools

## **Product Codes**

Tag: ZLAMT-3100A2P Tack: MJ200-B

## **Product Compatibility**

MXVT15: Versa Tie MJ200L-W: Long Tack MJVT-2: Versa Tack MJVT-3: Versa Tack MJVT-4: Versa Tack MXVT15: Versatie MXSTL: Lanyard-21cm (8.27in) MXGL: Lanyard-19cm (7.5in)

#### **Detachers**

SuperTag Detacher SuperTag Manual Handheld Detacher

#### **Detacher Type**

SuperTag

### **Environmental Constraints**

#### **Temperature**

Maximum storage temperature not to exceed 66°C (150°F) for 96 hours at 80% RH.

## Humidity

Unaffected by 80% humidity at 66°C (150°F), up to 96 hours.

## **Specifications**

Color	Black
Length	88mm (3.46in)
Width	31mm (1.22in)
Depth	21mm (0.83in)
Weight	22g (0.77oz)
Pullout Force	63.50kg (140lbs)

 $\mathsf{C}\,\mathsf{E}$  This product is in conformity with RoHS II Directive 2011/65/EU and REACH Substances of Very High Concern as defined in Regulation (EC) No 1907/2006 and subsequent amendments to both.