

Technical Specifications

APC Back-UPS 350, 230V | BK350EI | Downloaded on 03/27/2019 (EST)



APC Back-UPS 350, 230V

BK350EI

In Stock

159,89 €*

Price inclusive of VAT

- Battery Backup & Surge Protector for Electronics and Computers
- Includes: CD with software, Documentation CD, Installation manual in Japanese, Qty 1 - Detachable 1.2 m IEC power cord, Qty 1- Detachable IEC Power Cord, Telephone Cable, USB cable, Warranty card

Output

Output power capacity	210Watts / 350VA
Max Configurable Power (Watts)	210Watts / 350VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	47 - 63 Hz
Output Frequency (not synced)	50/60 Hz +/-1 Hz
Topology	Standby
Output Connections	(2) IEC Jumpers (Battery Backup) (3) IEC 320 C13 (Battery Backup) (1) IEC 320 C13 (selector_surgetitle)
Transfer Time	6ms typical : 10ms maximum

Input

Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320-C14 inlet
Cord Length	1.16meters
Input voltage range for main operations	180 - 266V
Number of Power Cords	2
Maximum Input Current	7.0A


*Prices are indicative

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

APC Back-UPS 350, 230V | BK350EI | Downloaded on 03/27/2019 (EST)

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	6hour(s)
Replacement Battery	RBC2 
Expected Battery Life (years)	4 - 6
RBC Quantity	1
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management

Interface Port(s)	Optional Simple Signalling RS232 cable, USB
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	310Joules
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ-45 connector)
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height	165MM, 16.5CM
Maximum Width	91MM, 9.1CM
Maximum Depth	284MM, 28.4CM
Net Weight	6.32KG
Shipping weight	7.05KG
Shipping Height	178MM, 17.8CM
Shipping Width	241MM, 24.1CM
Shipping Depth	368MM, 36.8CM
Color	Beige
Master Carton Units	2.0

*Prices are indicative

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Technical Specifications

APC Back-UPS 350, 230V | BK350EI | Downloaded on 03/27/2019 (EST)

Physical	
Units per Pallet	48.0
SCC Codes	1073130401634 9
Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters
Online thermal dissipation	19.0BTU/hr
Conformance	
Approvals	C-tick, CE, EN 50091-1, EN 50091-2, GOST, VDE
Equipment protection policy	Lifetime : 100000 Euro, Lifetime : 50000 GBP
Standard warranty	2 years repair or replace
Sustainable Offer Status	
RoHS	Compliant
PEP	Available in Documentation tab
EOL	Available in Documentation tab

*Prices are indicative

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.