

## Technical Specifications

APC Smart-UPS 1000VA LCD 230V | SMT1000I | Downloaded on 03/27/2019 (EST)



## APC Smart-UPS 1000VA LCD 230V

### SMT1000I

Call for More Information (0) 2 617 5555

- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
- Includes: CD with software, Documentation CD, Installation guide, Smart UPS signalling RS-232 cable, USB cable

### Output

|                                  |  |
|----------------------------------|--|
| Output power capacity            | 700Watts / 1.0kVA  |
| Max Configurable Power (Watts)   | 700Watts / 1.0kVA  |
| Nominal Output Voltage           | 230V   |
| Output Voltage Note              | Configurable for 220 : 230 or 240 nominal output voltage             |
| Output Voltage Distortion        | Less than 5% at full load  |
| Output Frequency (sync to mains) | 47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal           |
| Other Output Voltages            | 220, 240   |
| Topology                         | Line Interactive   |
| Waveform type                    | Sine wave  |
| Output Connections               | (8) IEC 320 C13 (Battery Backup)<br>(2) IEC Jumpers (Battery Backup) |

### Input

|  |                                  |
|--|----------------------------------|
| Nominal Input Voltage                              | 230V                             |
| Input frequency                                    | 50/60 Hz +/- 3 Hz (auto sensing) |
| Input Connections                                  | IEC-320 C14                      |
| Input voltage range for main operations            | 160 - 286V                       |
| Input voltage adjustable range for mains operation | 151 - 302V                       |
| Other Input Voltages                               | 220, 240                         |

### Batteries & Runtime


|              |  |
|--------------|--|
| Battery type | Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof |
|--------------|--|

**Disclaimer:** This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

## Technical Specifications

APC Smart-UPS 1000VA LCD 230V | SMT1000I | Downloaded on 03/27/2019 (EST)

### Batteries & Runtime

|                               |  |
|-------------------------------|--|
| Typical recharge time         | 3hour(s)   |
| Replacement Battery           | <a href="#">RBC6</a>              |
| Expected Battery Life (years) | 3 - 5  |
| RBC Quantity                  | 1  |
| Runtime                       | View Runtime Graph (Available in Technical Tab on site)<br>View Runtime Chart (Available in Technical Tab on site) |
| Efficiency                    | View Efficiency Graph (Available in Technical Tab on site)   |

### Communications & Management

|   |  |
|---|--|
| Interface Port(s)                       | RJ-45 Serial, SmartSlot, USB   |
| Control panel                           | Multi-function LCD status and control console  |
| Audible Alarm                           | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |
| Emergency Power Off (EPO)               | Optional   |
| Available SmartSlot™ Interface Quantity | 1  |

### Surge Protection and Filtering

|                     |   |
|---------------------|---|
| Surge energy rating | 459Joules   |
| Filtering           | Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping<br>response time : meets UL 1449 |

### Physical

|                  |               |
|------------------|---------------|
| Maximum Height   | 219MM, 21.9CM |
| Maximum Width    | 171MM, 17.1CM |
| Maximum Depth    | 439MM, 43.9CM |
| Net Weight       | 18.86KG       |
| Shipping weight  | 22.77KG       |
| Shipping Height  | 376MM, 37.6CM |
| Shipping Width   | 328MM, 32.8CM |
| Shipping Depth   | 595MM, 59.5CM |
| Color            | Black         |
| Units per Pallet | 12.0          |

**Disclaimer:** This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

## Technical Specifications

APC Smart-UPS 1000VA LCD 230V | SMT1000I | Downloaded on 03/27/2019 (EST)

| Environmental                                 |               |
|---|---------------|
| Operating Temperature                         | 0 - 40 °C     |
| Operating Relative Humidity                   | 0 - 95 %      |
| Operating Elevation                           | 0-3000meters  |
| Storage Temperature                           | -15 - 45 °C   |
| Storage Relative Humidity                     | 0 - 95 %      |
| Storage Elevation                             | 0-15000meters |
| Audible noise at 1 meter from surface of unit | 41.0dBA       |
| Online thermal dissipation                    | 100.0BTU/hr   |

| Conformance       |  |
|-------------------|--|
| Approvals         | CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE           |
| Standard warranty | 3 years repair or replace (excluding battery) and 2 year for battery |

| Sustainable Offer Status       |                                |
|--------------------------------|--------------------------------|
| RoHS                           | Compliant                      |
| REACH                          | REACH: Contains No SVHCs       |
| PEP                            | Available in Documentation tab |
| EOL                            | Available in Documentation tab |
| Other Environmental Compliance | China RoHS                     |

**Disclaimer:** This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.