FISCAL SUGGESTION









il Restaurants & Bars

Data Terminals

Ticketing

3 inch Impact Dot POS Printer

SRP-270



The BIXOLON SRP-270 is a high quality and reliable impact dot POS printer (spooler option). The SRP-270 is an ideal printer for point of sale and hospital ity applications. The modular user-friendly design, graphics capability, and 4.6 lps print speed offer reliable high performance in a compact, lightweight design. With the fast moving technology of today it is important to have simple integration of peripheral devices. The SRP-270 receipt printer is no exception; drivers are available for Windows and OPOS. Other features of the SRP-270 receipt printer include a paper end sensor that automatically alerts the user when the printer is out of paper, a tear-bar or auto-cutter, and the ability to print one original receipt plus two copies.

BR_SRP-270_EN_JUL19_V2
Copyright © BIXOLON Co., Ltd. All rights reserved.
Features and specifications are subject to change without prior notice.

PRINT CHARACTERISTICS

Print Method: 9 Pin / Serial Dot Matrix

Print Speed: Up to 4.6 lps

Print Resolution: 80 dpi (horizontal) / 144 dpi (vertical)

Print Width: Up to 63.5 mm Sensor: Paper End

MEDIA CHARACTERISTICS

Media Type: Receipt Media Width: 76.5 mm

Media Roll Diameter: Up to 83 mm Media Thickness: 0.06 ~ 0.085 mm Supply Method: Easy Paper Loading PHYSICAL CHARACTERISTICS

Dimensions (W x D x H): 160 x 249 x 130(A)/149(C)/160(D) mm (6.29 x 9.80 x 5.11(A)/5.86(C)/6.29(D) inch)

Weight: 2.3 kg (5.07 lbs.)

Electrical: External Power Adaptor 100-240V AV, 50/60Hz

Drawer Port: 2 ports (via y-type adaptor) **PERFORMANCE CHARACTERISTICS**

Receive Buffer: 4 Kbytes User Define Buffer: 17 Kbytes

Interface: USB V1.1 FS, Serial, Parallel, Ethernet

ENVIRONMENT CHARACTERISTICS

Temperature: Operating: $0 \sim 40$ (32 ~ 104)

Storage: -20 ~ 60 (-4 ~ 140)

Humidity: Operating: 10 ~ 80% RH Storage: 10 ~ 90% RH

RELIABILITY

Thermal Print Head (TPH): 300 Million Dots/Wire

Auto Cutter: 0.5 Million Cuts

SOFTWARE

Emulation: BXL/POS

Driver / Utility: Windows Driver, OPOS Driver,

Linux / Mac CUPS Driver,

Virtual COM USB / Ethernet Driver, Utility Program

SDK / Plugin: Linux SDK

FONTS / GRAPHICS / SYMBOLOGIES

Character Size: Font A: 9 x 9 Font B: 7 x 9

KOR: 17 x 9 CHN: 16 x 16

Characters Per Line: Font A: 33 Font B: 40

KOR: 20 CHN: 22

Character Sets: Alphanumeric: 95

Extended Graphics: 128 x 7 page

International: 32

Graphics: Supporting user-defined fonts, graphics, formats,

and logos

ACCESSORIES

Optional Accessories: Ribbon Cartridge, B-Melodist