

# TP-3260VL

## Thermal Receipt Printer

### Fast, Reliable and Easy To Configure

The TP-3260VL is the ergonomic designed POS thermal printer. It is fast, reliable, easy to configure and supports all the leading mobile operating systems. It features fast printing up to 300mm/second, trusted reliability, is perfect for use in retail, restaurant, office or bank environments.



- ✓ ESC/POS command sets compatible
- ✓ Interface: serial +USB+100M Ethernet standard
- ✓ Support Network Auto-reconnection after disconnect
- ✓ Support black mark media printing
- ✓ Built-in Web IP tools
- ✓ Support 2D barcode printing - QR code
- ✓ Support Windows 32/64bits / Linux / OPOS

# TP-3260VL

## Mechanical

Print Method	Direct thermal line
Printing Width	64mm or 72mm
Printing Speed	300mm/second
Auto Cutter	Full or Partial Cut
Dot Density	512dot/line or 576dot/line
Paper	79.5±0.5mm (width), 0.06~0.08mm (thickness), 80mm (roll diameter)
Interface	Serial+USB+Ethernet
Command	ESC/POS command
Character Size	ANK Font, Font A: 1.5x3.0mm (12x24dots), Font B: 1.1x2.1mm (9x17dots), Chinese Font
Data Buffer	128k bytes
Barcode Type	UPC-A /UPC-E /EAN13 /EAN8 /CODE39 /ITF /CODEBAR /CODE93 /CODE128 / QR Code
Operating Temperature	0°C to 45°C (operating); -10°C to 60°C (storage)
Print Head Life	100km
Cutter Life	1.5 million cuts
Weight	1.5kg

## Electrical

Power Input	DC 24V/2.5A
Power Supply Input	AC 110V/220V, 50-60Hz
Cash Drawer Input	DC 24V/1A

[Notice] : Specification are subject to change without notice

\*The instructions are all under the laboratorial measurements with specified paper.

For more information : [www.code-soft.com](http://www.code-soft.com)

**Code Soft International Information Co. Ltd.**

Room 319, Block C, The NEW Generation Info Tech Park, Chuangye Road, No.139, Bao'An District, Shenzhen, P.R.China.