

TCP-i500L

All-in-One POS Terminal



✓ 9.7", 12.1" & 15" second display supported



✓ Easy swap HDD for easy maintenance



✓ Optional peripherals MSR with finger print reader

TCP-i500L

Specification

CPU	Intel Celeron J1900 2.0 GHz Quad-Core or Intel Core i5-5200U 2.2GHz
Storage	64/128GB SSD or 500GB SATA HDD
Memory	4GB DDR3 (Max. 8GB)
Touch	Capacitive True-flat Touch
Display	15" TFT LED, 1024 x 768
Operating System	Windows 7, Windows 8, Windows 10, POSReady 7, Windows 10 IoT Enterprise

I/O Ports

USB	6
LPT	1
Serial (COM)	4
Network (LAN)	1 (RJ45)
VGA	1
Line In / Out	1 / 1
Mic	1

Optional Peripheral

MSR	ISO Track 1/2/3
Second Display	9.7", 12.1" or 15" (without touch or with capacitive touch)
Customer Display	VFD display 2 x 20 characters
MSR Fingerprint Module	ISO Track 1/2/3 MSR with Fingerprint Reader
Wifi Module	802.11 a/b/g/n/ac WLAN card

Environment

Operating Temperature	5°C ~ 35°C
Storage Temperature	-10°C ~ 50°C

Electrical

Power Input	DC 12V/7.5A
Power Supply Input	AC 100V-240V, 50-60Hz, 1.5A

[Notice] : Specification are subject to change without notice