



The RF Food label delivers dependable performance and merchandise protection for high value foods such as meat, smallgoods, and seafood increasingly targeted by thieves. This label helps food retailers to improve on-shelf availability and increase sales.

Hidden under the price weigh label, if undeactivated protected merchandise goes through an RF electronic article surveillance (EAS) pedestal it will activate the alarm and alert personnel of an attempted theft. The label is food safe so there is no concern about whether it will damage food product. Available for in-store hand application, the RF Food Label can also be applied to merchandise at the point of manufacturing. This allows retailers to receive floor-ready merchandise with consistent label placement to help expedite receiving and selling floor fulfillment.

#### **Retailer Values**

- Provides dependable protection enabling food retailers to improve on-shelf availability and increase sales
- Protects merchandise by tagging at the point of manufacturing so merchandise arrives shelf-ready
- Permits open merchandising while combatting theft
- · Microwave (SGS) Certified
- · Indirect Food Contact (ISEGA) Certified



### **Product Codes**

XL40FL-CLR1KAL: Small RollXL40FL-CLR4KAL: Large Roll

# **Technology**

RF (8.2MHz +/- 5%)

## **Product Compatibility**

Sensormatic RF detection and deactivation devices.

## **Certifications**

Microwave (SGS)
Indirect Food Contact (ISEGA)

## **Environmental Constraints**

#### Temperature

18°-30°C (64°-86°F)

### Humidity

55% maximum

#### Shelf Life

Two years from date of manufacture when labels are stored between  $18^{\circ}-30^{\circ}\text{C}$  ( $64^{\circ}-86^{\circ}\text{F}$ ).

### Mode of Application

Small Roll:

Hand or Tabletop

Large Roll:

Automatic

### **Materials of Construction**

50μm AL+13μm CPP+10μm AL **Hot Melt Adhesive** H4185-adv Bostik

#### **Dimensions**

Width	
Thickness	0.20mm ± 0.015mmm (0.0078in ± 0.0006in)
Liner Width	42mm ± 1.0mm (1.65in ± 0.0394in)

Liner to Liner Spacing......2.45mm ± 0.5mm

 $(0.096in \pm 0.0197in)$ 

C € This product is in conformity with RoHS Directive 2011/65/EU, 2015/863/EU and REACH regulation as defined in EC No 1907/2006 and subsequent amendments.

Roll Specifications						
	Small Roll	Large Roll		Small Roll	Large Roll	
PRODUCT CODE	XL40FL-CLR1KAL	XL40FL-CLR4KAL	PRODUCT CODE	XL40FL-CLR1KAL	XL40FL-CLR4KAL	
Diameter of Core	76.2mm (3in) core	76.2mm (3in) core	External Carton Dimensions	31.9X31.8X23cm (12.56X12.52X9.06in)	23X23X23cm (9.06X9.06X9.06in)	
Max Roll Diameter	136mm (5.35in)	228mm (8.98in)	External Cubic Ft. Per Case	0.82	0.43	
Number Splices	3 maximum	6 maximum	Labels per Roll	1,000	4,000	
Roll Weight	0.44Kg (0.97lbs)	1.75Kg (3.86lbs)	Rolls Per Case	20	5	
Case Weight (gross)	9.77Kg (21.53lbs)	9.77Kg (21.53lbs)	Cases Per Pallet	42	84	

