

# Eaton 5PX UPS

Enterprise class battery backup with extended runtime designed for virtualized environments

## 5PX features and benefits:

**Extended Runtime:** Add up to four extended battery modules for maximum runtime.

Virtualization-ready: Available in convenient bundles with a network card and management software for rapid integration into your virtual environment.

**Efficiency:** Provides industry leading efficiency of up to 99 percent.

## Manageability:

- Energy metering: The 5PX meters energy consumption right down to the outlet segments. No other UPS in the industry offers this capability.
- UPS management: By integrating the Eaton Intelligent Power<sup>®</sup> Manager software, you can monitor and manage the power devices on your network.

LCD display: Eaton's next generation LCD offers a graphical interface which provides all critical UPS information in a single screen view.

More power: Protects more devices by providing 28 percent more wattage compared to traditional UPSs.

Battery life: Eaton's exclusive ABM® technology increases battery service life by 50 percent.

## **Intelligent Power Manager (IPM)**

By integrating IPM with the Eaton 5PX, you can:

- Remotely monitor and manage multiple devices across your network from a single interface; this can be integrated into an already existing platform, such as VMware, Microsoft or Citrix
- Suspend non-critical virtual machines, consolidate critical virtual machines and shut down unused servers to extend battery runtime.
- Set server power consumption limits for extended battery runtime with UCS management software

To learn more, please visit:

Eaton.com/intelligentpower

## Services and support

Eaton provides product support 24 hours a day, 7 days a week. From battery replacement to full UPS service plans, Eaton has one of the top service models in the industry.

## Three-year warranty

The 5PX warranty covers both the UPS and the batteries for three years.



The Eaton 5PX is an ENERGY STAR® qualified UPS. ENERGY STAR is intended to help consumers save money and protect the environment through energy efficient products and practices.



#### **5PX MODEL SELECTION GUIDE\***

| Catalog Number   | Rating (VA / watts) | Input connection             | Output receptacles      | Dimensions (H x W x D), in | Net weight, Ib |  |
|--|---------------------|------------------------------|-------------------------|----------------------------|----------------|--|
| 120V, 50/60 Hz   |                     |                              |                         |                            |                |  |
| 5PX1000RT  | 1000 / 1000         | 5-15P                        | (8) 5-15R<br>(8) 5-20R  | 3.4 x 17.4 x 20.6          | 62             |  |
| 5PX1500RT  | 1440 / 1440         |                              |                         |                            | 65             |  |
| 5PX2200RT  | 1950 / 1920         | 5-20P                        |                         |                            | 65             |  |
| 5PX3000RT2U  | 2000 / 2700         | L5-30P                       | (1) L5-30R<br>(6) 5-20R | 3.4 x 17.4 x 25.4          | 87             |  |
| 5PX3000RT3U  | 3000 / 2700         | L5-30P                       |                         | 5.1 x 17.4 x 19.6          | 86             |  |
| 208V/230V, 50/60 Hz  |                     |                              |                         |                            |                |  |
| 5PX1500iRT   | 1500 / 1350         | C14-10A                      | (8) C13-10A             | 3.4 x 17.4 x 20.6          | 61             |  |
| 5PX2200iRT   | 2200 / 1980         | C20, 10 A                    | (1) C19-16A             | 3.4 x 17.4 x 20.6          | 63             |  |
| 5PX3000iRT2U   | 3000 / 2700         | C20-16A                      | (8) C13-10A             | 3.4 x 17.4 x 25.4          | 84             |  |
| 120V, 50/60 Hz Virtualization-ready bundles with Network Card-MS     |                     |                              |                         |                            |                |  |
| 5PX1500RTN   | 1440 / 1440         | 5-15P                        | (8) 5-15R               | 3.4 x 17.4 x 20.6          | 65             |  |
| 5PX2200RTN   | 1950 / 1920         | 5-20P                        | (8) 5-20R               | 3.4 x 17.4 x 20.6          | 65             |  |
| 5PX3000RTN   | 3000 / 2700         | L5-30P                       | (6) 5-20R, (1) L5-30R   | 3.4 x 17.4 x 25.4          | 87             |  |
| 208/230V, 50/60 Hz Virtualization-ready bundles with Network Card-MS |                     |                              |                         |                            |                |  |
| 5PX3000iRTN  | 3000 / 2700         | C20                          | (8) C13, (1) C19        | 3.4 x 17.4 x 25.4          | 84             |  |
| Extended Battery Modules   | DC voltage          | For use with                 | Max qty / UPS           | Dimensions (H x W x D), in | Net weight, lb |  |
| 5PXEBM48RT   | 48V                 | All 1000, 1500 & 2200 models |                         | 3.4 x 17.4 x 20.6          | 72             |  |
| 5PXEBM72RT2U   | 701/                | All 3000 2U models           | 4                       | 3.4 x 17.4 x 25.4          | 102            |  |
| 5PXEBM72RT3U   | - 72V               | All 3000 3U models           |                         | 5.1 x 17.4 x 19.6          | 98             |  |

<sup>\*</sup>Due to continuous product improvement programs, all specifications are subject to change without notice. Please visit Eaton.com/5PX to view complete and updated product specifications.

| Additional Options   | Catalog Number   | For use with                          |  |  |  |  |
|--|------------------|---------------------------------------|--|--|--|--|
| Connectivity   |                  |                                       |  |  |  |  |
| Network Card-MS  | NETWORK-MS       | All models*                           |  |  |  |  |
| Environmental Monitoring Probe   | 116750224-001    | All models (requires Network Card-MS) |  |  |  |  |
| Power Distribution & Bypass  |                  |                                       |  |  |  |  |
| HotSwap Maintenance Bypass (MBP)   | EHBPL1500R-PDU1U | All 1000 & 1500 models                |  |  |  |  |
| The HotSwap Maintenance Bypass allows you to exchange or service the UPS without | EHBPL2000R-PDU1U | All 2200 models                       |  |  |  |  |
| shutting down the connected load   | EHBPL3000R-PDU1U | All 3000 models                       |  |  |  |  |
| Mounting Hardware  |                  |                                       |  |  |  |  |
| 2-post rail kit  | 103007018-5591   | All models                            |  |  |  |  |

#### What's in the box

- Tower pedestals
- Four-post rail kit
- User manual CD
- Quick start guide
- USB cable
- RS-232 serial cable
- Phillips Head screw driver
- 2 IEC to IEC jumper cables (208V/230V models)



#### Eaton

1000 Eaton Boulevard Cleveland, OH 44122 United States Eaton.com

Eaton.com/powerquality

©2017 Eaton All Rights Reserved Printed in USA 5PX01FXA / GG August 2017



Eaton, Intelligent Power and ABM are registered trademarks.

All other trademarks are property of their respective owners.

ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. ENERGY STAR is a registered mark owned by the U.S. government.

