

# TCP-M156

## All-in-One POS Terminal

### Reliable and Flexible

The TCP-M156 is an ergonomic design POS Terminal. The low power consumption CPU with reliable and durable architecture design to provide better POS solution on the market. Quick access to the hard drive disk to help you reducing your service cost and time. This terminal can matched your desire of high value POS solution.



- Low-power consumption CPU, reliability and flexibility POS Terminal
- Various peripherals - VFD, Multiple Size of Second Display and MSR

# TCP-M156

## Specification

CPU	Intel Celeron J1900 quad-core 2.0 GHz	i5-4210U dual-core 1.7GHz
Colour	Black	
Memory	4GB DDR3	
Storage	M100-128GB Dual Channel (SATA 3 Gbps x 1 + mSATA(3) x1)	
Main Board	Baytrail mother board	
Display	15.6" TFT touch screen	
Touch Panel	10 points capacitive touch panel	
Resolution	1366 x 768	
Operating System	Windows 7 / 8 / 10 / IoT 10	

## I/O Ports

USB 2.0	6	4
Serial Port	1	-
LAN Port	1	1
Ethernet	Realek PCI-E NIC RTL 8111E for 1000M bps	
Audio Port	1	1
Audio	Realtek ALC662 5.1 Channel HDA Codec , Support MIC/Line-out Ports 1* Amplifier	
VGA	-	1
HDMI	-	1

## Peripheral

Optional Build-in Peripheral	MSR, VFD, Second Display & WiFi
------------------------------	---------------------------------

## Environment

Operating Temperature	0°C ~ 60°C
Storage Temperature	-10°C ~ 70°C
Certificate	CE / ROHS / FCC

## Electrical

Power Supply Input / Output	AC 100V-240V, 50-60Hz, DC12V / 5A
-----------------------------	-----------------------------------

[Notice] : Specification are subject to change without notice