



**NQuire 1000
Manta**
Micro Kiosks

Features

Fully functioning CIT system.

With Octa-Core Cortex-A53 CPU up to 1.5GHz.

Easy to install and use anywhere.

Ideally suited for shelf mounting or on-counter usage in department stores, supermarkets, small grocery stores, pharmacy/cosmetic stores, tobacco kiosks and more.

Snappy reading performance.

Armed with Newland's EM2037-V4, 2D megapixel barcode scanner. The engine has a 20 degree scan angle for comfortable scanning of larger products. Also, available without a scanner.

Easily build applications.

The NQuire 1000 Manta is built on Android 7.1, allowing for easy development of custom applications, tailored to your needs.

Highly customizable with a broad range of features.

Dual band WiFi, Bluetooth embedded, front 5Mp camera, POE, speaker.

Variety of mounting accessories.

Foldable desktop stand, VESA magnetic shelf stand, VESA wall mount.



Suggested industries



Industrial



Manufacturing



Public Sector



Retail



Tourism

Nquire 1000 Manta Technical specifications

Performance

Image Sensor	CMOS 1280*800
Operating System	Android 7.1
Processor	RK3368, Octa-core Cortex-A53; up to 1.5 GHz , PowerVR G6110 GPU; up to 600MHZ
Memory RAM	2GB DDR3
Memory Flash	8GB Emmc
Illumination	Red LED(625±10 nm)
Aiming	Red LED(625±10 nm)
Minimal Print Contrast	25%
Scan Angle Roll	360°
Scan Angle Pitch	±55°
Scan Angle Skew	±55°
Field of View Horizontal	39°
Field of View Vertical	24°
Scan Modes	Sense Mode
Scan Rate	60 frames per second

Data Capture

1D	All major 1D symbologies, including Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, Code 93, UCC/EAN-128, GS1 Databar, GS1 Composite Code, Matrix 2 of 5, Code 11, Industrial 25, Standard 25, Plessey, MSI-Plessey.
2D	All major 2D symbologies, including PDF417, QR Code, Data Matrix, Chinese Sensible Code, Aztec Code, Maxicode, MicroPDF417.

Physical

Dimensions (mm)	252 × 184 × 33mm
Weight	615 g
Material	PC, ABS
VESA standard	Metal Fitting mounting screw holes: 75*75 mm
Display	10.1" WXGA, 1280*800 TFT LCD display
Touch Panel	10 points Capacitive Touch
Buttons	(Vol+ / Vol-) / (Up / Down) / Exit / Power switch
Interfaces	USB 2.0 port, type A port, GPIO port
Input Voltage	DC12V±5%
Power Supply Input	DC12V, 2A
Power Supply Output	AC100~240V, 50~60Hz
Sensors	G Sensor
Power over Ethernet	802.3af
Audio	1x 3.5mm Headset + MIC jack, 2x Integrated speakers 8Ω / 1.3W
Audio Jack	3.5mm earphone

Newland EMEA HQ

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2021, all rights reserved

NQuire 1000 Manta Technical specifications

Pogo Pin	2x POGO-PIN
Expansion Slot	SD card
Camera	Front: 5.0 MP camera
Video	MKV, TS, FLV, AVI, VOB, MPG, DAT, ASF, RM, MOV, 3GP, MP4, WMV

Environmental

Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-10°C to 55°C (14°F to 131°F)
Humidity	20% to 65% (40°C)
IP Rating	IP54

Wireless

WLAN RADIO	IEEE 802.11 b/g/n/ac (2.4G), IEEE 802.11 a/b/g/n/ac (5G)
WPAN RADIO	Bluetooth 4.1
RFID	Optional

Accessories

Standard	Multi-pin, multi-plug AC/DC adapter with power cord
Optional	VESA 75 Wall Mount

Software

MDM (certified)	Ndevor, SOTI
Terminal Emulation (compatible)	Airwatch
Configuration Tools	Ndevor

Certifications

Hardware	CE, FCC, RoHS
----------	---------------

Warranty

Standard	2 years
----------	---------

Newland EMEA HQ

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2021, all rights reserved