



Model : KTP-215M-002-01

V 2.0

Open Frame Touch Computer Features

- **Antibacterial**
- **Integrated with KeeTouch PCAP touch panel for the ultimate in image quality**
- **Support Android, Windows and other systems**
- **High quality panel with high brightness, contrast ratio and broad viewing angle**
- **Worldwide agency approvals**

Specification

Complete Machine

Model No.	KTP-215M-002-01	
Series	Antibacterial Touch Computer	
Display Type	16:9 Ratio 21.5" TFT-LCD	
Active Area	476.64mm x 268.11mm	
Monitor Dimensions (W*H*D)	518*313*58 (mm)	
Suggested Resolution	1920*1080 @ 60Hz	
Support Colors	16.7M	
Brightness (Typ.)	Pure LCD Panel	250cd/m2
	With Cover Glass	212cd/m2
Response Time (Typ.)	25ms	
Viewing Angle(Typ.at CR > 10))	Horizontal(left/right)	89°/89°
	Vertical(up/down)	89°/89°
Contrast Ratio (Typ.)	3000:1	
Power Supply	Type: External brick Input (line) voltage: 100-240 VAC, 50-60 Hz	
Environment	Operating Temp.	0 ~ 50°C
	Operating RH	20% ~ 80%
	Storage Temp.	-10 ~ 60°C
	Storage RH	10% ~ 90%
Mount Interface	VESA 75mm and 100mm	
Agency approvals	CCC, ETL, FCC, CE, CB, RoHS	
Computer parameters	CPU	Intel Core™ I5
	RAM	8GB
	SSD	EMMC 256GB
	I/O interface:	2-COM, 4-USB,2-LAN RJ45,1-HDMI,1-Audio/Mic(1-3.5mm line-out and mic-in)
Touch typ	21.5" PCAP 10-Point multi - touch	
MTBF	30,000 Hours	
Back light Life(Typ.)	30,000 Hours	
Weight (N.W/G.W)	N.W:6.2Kg (single) /G.W:14.1Kg (2pcs in one package)	
Package Dimensions	675LX480HX230W mm (2pcs in one package)	
Power Consumption	35W(APPROX)	
Standby power consumption	0.80W (APPROX)	
Touch screen Type	21.5" Projected Capacitive Touchscreen, 10 points in win7	
Regular Warranty	1 year	

NOTE :

- ① The display SPEC. are adjusted according to the selected LCD screen and touch screen
- ② The support system is adjusted according the specific system and version.

Mechanical Dimensions

