











5G PORTABLE DATA COLLECTOR

FEATURES

O 6" Full Screen Display Experience

6.1" HD display screen, support multi-point capacitive touch screen, design with Gorilla Glass to provide better drop performance and higher resistance to scratch.

Large Capacity Battery and **Super-Fast Charging**

The NLS-MT95 is equipped with a 6000mAh battery, supplemented by a low power design, which significantly extends the usage time. Besides, it supports fast charging with a Type-C port, and the charging power is up to 18W.

Rugged Durability

The NLS-MT95's rugged housing is sealed to IP67 standards for protection against dust and water and withstands 1.5m drops to concrete.

Powerful Performance

The NLS-MT95 comes with Android 11 operating system and is powered by a 2.2GHz octa-core processor. It supports ViLte and 5G dual SIM dual standby for full Netcom to meet various application needs.

















NLS-MT95

Performance		
Processor		2.2GHz, octa-core 64-bit processor
Operating System		Android 11
Memory		4GB RAM, 64GB ROM
Symbologies	2D	Aztec, Composite, CS Code, Maxicode, Micro PDF, Micro QR, PDF 417, QR Code, Data Matr DotCode.
	1D	Code128, Code 49, Code 16K, (GS1128) UCC/EAN-128, AIM-128, EAN-8, EAN-13, UPC-E, UPC ITF, ITF 6, ITF 14, Matrix 2 of 5, Industrial 25, Standard 2 of 5, Code39, ISSN, ISBN, CodaBc Code93, Code 11, Plessey, MSI Plessey, RSS.
Depth of Field	EAN-13	70mm-600mm(13mil)
(Depend on Barcode and Environment)	Code39	120mm-280mm(5mil)
	PDF17	110mm-230mm(6.7mil)
	Data Matrix	110mm-260mm(10mil)
	QR Code	55mm-400mm(15mil)
Physical/Electrical	•	
Dimensions (L×W×H)		165(L) × 78.5(W) × 15.5(H) mm
Weight		287g (including battery)
Display		6.1" (720×1560), Gorilla Glass screen
Keypad		5 keys(side keys included)
Notification		Vibrator, speaker and multi-color LEDs
Battery		3.85V, 6000mAh
GPS		GPS (AGPS), GLONASS, Beidou, Galileo
Camera		Front camera: 8 megapixels, fixed focus
		Rear camera: 13 megapixels, auto focus, with LED flashlight
Expansion		Build in TF Card (optional)
Card Slots		Nano+Nano
Interface		Type-C 2.0 OTG, Type-C earphone
AC Adapter		18W Fast Charging Supported
Sensors		Light & Proximity sensor, accelerometer sensor, magnetic sensor, gyroscope sensor
Environmental		
Operating Temperature		-20°C to 50°C (-4°F to 122°F)
Storage Temperature		-30°C to 60°C (-22°F to 140°F)
Humidity		5% to 95% (non-condensing)
Static Discharge		±15 kV (Air discharge), ±8 kV (Direct discharge)
Drop		1.5m drops to concrete (for six sides, one drop per side)
Sealing		IP67
NFC		
13.56MHz RFID		ISO14443A/B, ISO15693, ISO18000-3, MIFARE, FeliCa RF, Kovio, NFC Forum Type 1-4 Tags
Wireless		
WLAN RADIO WWAN RADIO(For 4G Version)	2G	Built-in 802.11 a/b/g/n/ac, support 2.4G and 5G dual frequency GSM (B2, B3, B5, B8)
	3G	WCDMA (B1, B2, B5, B8); CDMA: 1X EVDO (BC0)

WCDMA (B1, B2, B5, B8); CDMA: 1X EVDO (BC0)

4G TDD-LTE (B34, B38, B39, B40, B41)

FDD-LTE (B1, B2, B3, B5, B7, B8, B20, B28 a&b)

5G NR (N1/3/8/28/38/41/77/78/79)

WPAN RADIO Bluetooth 5.2

Accessory (Optional)

AC adapter, cable