

Thermal Slip Printer

NITA

D300H

Printing speed : 300 mm/sec
Interface : USB + LAN + RS232



Features

- Front paper loading, vertical printing
- 300 MM/S printing speed
- Serial (RS232) + USB + LAN interface
- Built in web page to set up printer directly
- Printer status monitoring
- Input buffer 2048K bytes
- Support QR CODE printing
- Support LINUX, Windows system
- Support 58 MM and 80 MM paper roll printing



NITA D300H

'NITA D300H' is new generation of receipt printer, waterproof, oilproof and dustproof design. With auto cutter and compatible with several operation systems.

Printing Preference

Printing	D300H
Printing method	Direct thermal
Print width	76mm
Column capacity	512 dots/line
Printing speed	300mm/s
Interface	USB+Serial+Lan
Printing paper	79.5±0.5mm×φ80mm
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/Chinese,traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A:1.5×3.0mm (12×24 dots) Font B:1.1×2.1mm (9×17 dots) Chinese,traditional Chinese:3.0×3.0mm (24×24 dots)

Cutter

Auto cutter	Partial
-------------	---------

Barcode Character

Extension character sheet	PC347 (Standard Europe)、Katakana、PC850 (Multilingual)、PC860 Portuguese)、PC863 (Canadian-French)、PC865 (Nordic)、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2)、PC852 (Latin2)、PC858、IranII、Latvian、Arabic、PT151 (1251)
Barcode types	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/ CODE93/CODE128 /QR CODE / PDF417

Buffer

Input buffer	2048k bytes
NV Flash	256k bytes

Power

Power adaptor	Input: AC 110V/220V, 50-60Hz
Power source	Output: DC 24V/2.5A
Cash drawer output	DC 24V/1A

Physical characteristics

Weight	1.78KG
Dimensions	198×148×138mm (D×W×H)
Work environment	Temperature (0-45) humidity(10-80%)
Storage environment	Temperature(-10-60 C) humidity(10-80%)
Cutter life	1.5 million cuts
Printer head life	100KM