

Safety Data Sheet

Section 1 : Product and company identification

Product code : NW0055F
Product descriptions : **FASSON®** Direct Thermal 200GP FSC/S1010/BG40Wh Imp
Product use : Self-adhesive label
Manufacturer : 110/1 Moo 1 T.Srisajorakhe Yai,
A.Bangsaothong, Samutprakarn 10540, Thailand
Tel. (66)-2-740-4666
Fax. (66)-2-740-4626

Information contacts : Please contact our sales representative

Section 2 : Composition and information on components

Component	CAS Number	OSHA Hazard (Yes / No)	Percent by Weight	Exposure Limit
Facestock	65996-61-4	No	40 – 50	Not established
Adhesive	9063-87-0	No	10 – 20	Not established
Release Liner	65996-61-4	No	35 – 45	Not established

Section 3 : Hazardous identification

This product contains no hazardous ingredients as defined under OSHA 1900.1200

Section 4 : First aid measures

This product is an article. Exposure is not expected. Cuts possibly happen when handling

This product First aid should be provided at any cut or abrasion.

- Eye : N/A
- Skin : N/A
- Inhalation : N/A
- Ingestion : N/A

Product: NW0055F

Section 5 : Fire fighting measures

- Flash point : N/A
- LEL : N/A
- UEL : N/A
- Extinguish media
 - Use foam, carbon dioxide or water spray when fighting fires involving this material.
- Firefighting instructions
 - As in any fire, wear self-contained breathing apparatus and full protection gear.
- Unusual hazards
 - Combustion of this material may evolve with carbon monoxide.

Section 6 : Accidental release measures

- Spill or release procedures
 - This product is an article. No spill or release is expected.

Section 7 : Handling and storage

- Handling
 - Lift with proper handling techniques.
- Storage
 - Store in a cool and dry area.

Section 8 : Exposure control / Personal protection

- Engineering controls
 - Provide adequate mechanical ventilation when processing this material.
- Personal protective equipment
 - General : Gloves
 - Eye / Face protection : N/A
 - Skin protection : Cotton or leather gloves
 - Respiratory : N/A

Section 9 : Physical and chemical properties

Adhesive properties: A general purpose permanent emulsion acrylic adhesive.

Facestock properties: FSC certified, smooth white woodfree paper.

Liner properties: High-density glassine paper.

- **Section 10 : Stability and reactivity**
- Chemical stability : Stable
- Incompatibility with other materials : Elevated temperatures, heat and sparks.

Product: NW0055F



- Hazardous decomposition products : Carbon monoxide
- Hazardous polymerization : Will not occur

Section 11 : Toxicological Information

No toxicological studies have been performed on this product.

Section 12 : Ecological Information

No ecological studies have been performed on this product.

Section 13 : Disposal Considerations

Dispose of in accordance with government and local regulations.

Section 14 : Transport information

Not regulated under Department of Transportation (DOT).

Disclaimer : The information and recommendations contained herein upon data believed to be correct. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained herein. This document is furnished for product information only. This product is considered an article which is exempt under the OSHA HCS 1900.1200.

Product: NW0055F